

AddRecordToRecordset

(Q) How to add a record to a recordset

tags:
[HowTo](#)

(R) To add a record to a **Recordset object**:

- Use the **AddNew** method to create a record you can edit.
- Assign values to each of the record's fields.
- Use the **Update** method to save the new record.

The following code example adds a record to a Recordset associated with a table called Shippers.

- Shippers table

Fields	Field Type	Primary
CompanyName	Text	
Phone	Text	
ShipperID	BigInt	Y

```
Dim odbNorthwind As Object
Dim orsShippers As Object

Set odbNorthwind = Application.CurrentDb
Set orsShippers = odbNorthwind.OpenRecordset("Shippers")

With orsShippers
    .AddNew
    .Fields("CompanyName").Value = "Global Open Source Service"
    '
    ' Set remaining fields.
    '
    .Update
    .mClose()
End With
```

When you use the *AddNew* method, *Access2Base* prepares a new, blank record, initializes its fields to their default value and makes it the current record. When you use the *Update* method to save the new record, the record that was current before you used the *AddNew* method becomes the current record again.

If you use the *AddNew* method to add a record, and then move to another record or close the *Recordset* without first using the *Update* method, your changes are lost without warning. For example, omitting the **Update** method from the preceding example results in no changes being made to the Shippers table.

See also

[OpenRecordset Value \(field\)](#)

Refer to ...

Basic module	Sub	Comments
HowTo	AddRecordToShippers	

Bookmark this page » » [AddRecordToRecordset](#)