

Home Install Full Index Tutorial EnumerateControls FindOutTableExists
 UseVariablesInSQL CreateRecordsetFrom AddRecordToRecordset CountRecordsRecordset
 LimitsRecordset MixAccess2baseAndUNO User's Guide AllForms DatabaseWindow
 ShortcutNotationMore DLookupSamples CalculatedField MultiSelectListboxSelectForm
 FillAutoControlValue CarryToNewRecord BrowseThruControls TipTextForLongValues
 AskBeforeSaving Sync2Combos ZoomOnImage AddAllToBox KeepFormsSynchro
 SelectListboxOnFirstLetters MoveItemsBetweenListboxes SimulateTabbed SearchStandalone
 CalculatorDialog ExploreTables ExtractDataTable FindPositionRecordset DMedian function
 DPercentile ImportImages ExportImages CrossTabQuery DbaccessFromCalc
 Standalone Forms Add AddItem AddNew CancelUpdate Clone Close (method)
 CloseAllRecordsets CloseConnection CreateField CreateQueryDef CreateTableDef

CreateTableDef

Creates a new **TableDef object** in the current **database**.

This method offers the capacity to create from the Basic code a new table independently from the underlying RDBMS. Thus without using SQL. However only a limited set of options are available for field descriptions.

tags:
Methods

Applies to ...

Object	Description
Database	The representation of the database currently connected to a Base ("*.odb") document.

Syntax

Set *tabledef* = *database*.CreateTableDef(*name*)

Arguments - Returned value

Argument	Type	Optional	Description	Returned value
<i>name</i>	String	N	The name of the new table	A tabledef object

Remarks

- The *CreateTableDef* method may be applied ONLY from a macro executed from a Base ("*.odb") document, said otherwise, not from a standalone form. The *database* object should be returned by the **Application.CurrentDb** method.
- To become fully viable the new *TableDef* object has to be **added** explicitly to the **TableDefs collection**.
- Between the execution of the *CreateTableDef* and the *Add* methods one or more fields should have been created thru the **CreateField** method.
- If the object specified by *name* is already a member of the *TableDefs* collection (the comparison is NOT case-sensitive !!), the existing table is erased without warning.

Error messages

Argument nr. ... [Value = '...'] is invalid
Method 'Database.CreateTableDef' not applicable in this context

See also

[Add](#)
[CreateField](#)
[CreateQueryDef](#)
[TableDefs](#)
[TableDef](#)
[QueryDefs](#)
[QueryDef](#)

Example

Build a new table in the database without using SQL

```
Dim oDatabase As Object, oTable As Object
    Set oDatabase = Application.CurrentDb()
    Set oTable = oDatabase.CreateTableDef("myNewTable")          ' Create
    With oTable
        .CreateField("myAutoIncrFld", dbLong, , dbAutoIncrField)   ' Create
        .CreateField("myDecimalFld", dbDecimal, 10.4)
    End With
    oDatabase.TableDefs().Add(oTable)                            ' Final
```

Add a field to an existing table

```
Set oTable = oDatabase.TableDefs("myExistingTable")
oTable.CreateField("myBinaryFld", dbBinary)
```

[Bookmark this page » » CreateTableDef](#)