

Home ✕ Install ✕ Full Index ✕ Tutorial ✕ EnumerateControls ✕ FindOutTableExists ✕
 UseVariablesInSQL ✕ CreateRecordsetFrom ✕ AddRecordToRecordset ✕ CountRecordsRecordset ✕
 LimitsRecordset ✕ MixAccess2baseAndUNO ! User's Guide ✕ AllForms ✕ DatabaseWindow ✕
 ShortcutNotationMore ✕ DLookupSamples ✕ CalculatedField ✕ MultiSelectListboxSelectForm ✕
 FillAutoControlValue ✕ CarryToNewRecord ✕ BrowseThruControls ✕ TipTextForLongValues ✕
 AskBeforeSaving ✕ Sync2Combos ✕ ZoomOnImage ✕ AddAllToBox ✕ KeepFormsSynchro ✕
 SelectListboxOnFirstLetters ✕ MoveItemsBetweenListboxes ✕ SimulateTabbed ✕ SearchStandalone ✕
 CalculatorDialog ✕ ExploreTables ✕ ExtractDataTable ✕ FindPositionRecordset ✕ DMedian function ✕
 DPercentile ✕ ImportImages ✕ ExportImages ✕ CrossTabQuery ✕ DbaccessFromCalc ✕
 Standalone Forms ✕ Add ✕ AddItem ✕ AddNew ✕ CancelUpdate ✕ Clone ✕ Close (method) ✕
 CloseAllRecordsets ✕ CloseConnection ✕ CreateField ✕ CreateQueryDef ✕ CreateTableDef ✕
 CurrentDb ✕ Delete ✕ Delete (table-query) ✕ Edit ✕ EndExecute ✕ Execute (commandbarcontrol) ✕
 Execute (dialog) ✕ Execute (query) ✕ getProperty ✕ GetRows ✕ hasProperty ✕ Move ✕
 Move (recordset) ✕ OpenConnection ✕ OpenDatabase ✕ OpenRecordset ✕ OptionGroup (Method) ✕
 ReadAllBytes ✕ ReadAllText ✕ Refresh ✕ Remove ✕ RemoveAll ✕ RemoveItem ✕ Requery ✕
 Reset ✕ RunSQL ✕ SetFocus ✕ SetProperty ✕

setProperty

The `setProperty` method modifies the current value of any modifiable property of **objects**.

tags:
Methods

Applies to ...

Object	Description
Control	The representation of a control within a form, a subform, a gridcontrol or a dialog. The control may be any control type including a gridcontrol .
Field	Identifies a field within a <i>TableDef</i> , a <i>QueryDef</i> or a <i>Recordset</i>
Form	The representation of a database form
OptionGroup	Identifies a group of radio buttons within a form or a subform.
QueryDef	Corresponds with a query definition
Recordset	Identifies a set of records related to a table, a query or a SQL statement
SubForm	Identifies a specific control which is a subform of a database form or another subform
TempVar	Represents a temporary variable

Syntax

```

control.setProperty(property-name, value)
control.setProperty(property-name, value, index)
field.setProperty(property-name, value)
form.setProperty(property-name, value)
optiongroup.setProperty(property-name, value)
querydef.setProperty(property-name, value)
recordset.setProperty(property-name, value)
subform.setProperty(property-name, value)
tempvar.setProperty(property-name, value)

```

Applied to	Type	Argument #1	Type	Argument #2	Type	Argument #3	Type	Returned value
control	Control object	property-name	String	value	Variant	index	absent	True if success.
field	Field object						Integer	
form	Form object						Long	
optiongroup	Optiongroup object							

querydef	QueryDef object					
recordset	Recordset object					
subform	Subform object					
tempvar	Subform object					

Remarks

The *index* argument must have a (integer or long) value between 0 and the size of the array associated with the considered *property* - 1.

Error messages

Argument nr. ... [Value = '...'] is invalid
Property '...' not applicable in this context
Value '...' is invalid for property '...'
Out of array range or incorrect array size for property '...'

See also

[Property](#)
[Properties](#)
[hasProperty](#)
[getProperty](#)

Example

Set all enabled controls on a form in italic

```
Dim ofForm As Object, i As Integer, iCount As Integer, ocControl As Object
  Set ofForm = Forms("myForm")
  iCount = ofForm.Controls().Count
  For i = 0 To iCount - 1
    Set ocControl = ofForm.Controls(i)
    If ocControl.hasProperty("FONITALIC") Then
      If ocControl.hasProperty("ENABLED") Then
        If ocControl.Enabled Then ocControl.setProperty("FONITALIC", True)
      End If
    End If
  Next i
```

[Bookmark this page » » setProperty](#)