

## OpenTable

The *OpenTable* action opens a table in normal view or in table design view.

tags:  
**Actions**

### Applies to ...

Object	Description
<b>DoCmd</b>	Root class. When present, its name must be "DoCmd" but the object name is optional.

### Syntax

[DoCmd.]OpenTable(TableName, View, DataMode)

Argument	Optional	Type or Symbol	Description
TableName	No	String	The name of the table to open. This argument is NOT case-sensitive.
View	Yes	acViewDesign acViewNormal acViewPreview	The view in which the table will open. acViewNormal and acViewPreview are equivalent. Default is acViewNormal.
		acEdit	The user will be allowed to add new records and edit existing records.

The symbolic constants can be included in your code by copying and pasting next lines:

```
Const acViewDesign = 1
Const acViewNormal = 0
Const acViewPreview = 2

Const acEdit = 1
```

### Remarks

- If the *view* argument is *acDesign*, the table will get opened in Design mode. However any further action is not supported by the Access2Base API.
- The *OpenTable* action must not be triggered from a **standalone form**.

### Error messages

Table '...' could not be opened
Table '...' not found
Action not applicable in this context

### See also

[Close](#)  
[OpenForm](#)  
[OpenQuery](#)  
[OpenReport](#)  
[OpenSQL](#)

### Example

```
Const acViewNormal = 0  
OpenTable("myTable", acViewNormal)
```

Bookmark this page » » [OpenTable](#)